



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁵ : A23D 9/00, A23L 1/308 A23G 3/00, 9/02	A1	(11) International Publication Number: WO 93/00823 (43) International Publication Date: 21 January 1993 (21.01.93)
(21) International Application Number: PCT/EP92/01429 (22) International Filing Date: 25 June 1992 (25.06.92) (30) Priority data: 91201819.9 12 July 1991 (12.07.91) EP (34) Countries for which the regional or international application was filed: AT et al. 92200138.3 17 January 1992 (17.01.92) EP (34) Countries for which the regional or international application was filed: AT et al. (71) Applicant (for AT BE CH DE DK ES FR GR IT NL SE only): UNILEVER N.V. [NL/NL]; P.O. Box 137, NL-3000 DK Rotterdam (NL).		(71) Applicant (for GB only): UNILEVER PLC [GB/GB]; Unilever House, Blackfriars, London EC4P 4BQ (GB). (72) Inventor; and (75) Inventor/Applicant (for US only) : MÜLLER, Volkmar, Konrad [DE/NL]; Koekoeklaan 2, NL-2566 JS Den Haag (NL). (74) Agents: JOPPE, Hermina, Laura, Petronella et al.; Unilever N.V., Patent Division, P.O. Box 137, NL-3130 AC Vlaardingen (NL). (81) Designated States: US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, NL, SE). Published With international search report.
(54) Title: EDIBLE FAT-CONTAINING PRODUCTS (57) Abstract Mixtures of specific liquid and solid polyol fatty acid polyesters are believed to exhibit a favourable rheology and/or favourable anti anal leakage properties, and/or improved mouthfeel.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FI	Finland	MI	Mali
AU	Australia	FR	France	MN	Mongolia
BB	Barbados	GA	Gabon	MR	Mauritania
BE	Belgium	GB	United Kingdom	MW	Malawi
BF	Burkina Faso	GN	Guinea	NL	Netherlands
BG	Bulgaria	GR	Greece	NO	Norway
BJ	Benin	HU	Hungary	PL	Poland
BR	Brazil	IE	Ireland	RO	Romania
CA	Canada	IT	Italy	RU	Russian Federation
CF	Central African Republic	JP	Japan	SD	Sudan
CG	Congo	KP	Democratic People's Republic of Korea	SE	Sweden
CH	Switzerland			SN	Senegal
CI	Côte d'Ivoire	KR	Republic of Korea	SU	Soviet Union
CM	Cameroon	LI	Liechtenstein	TD	Chad
CS	Czechoslovakia	LK	Sri Lanka	TC	Togo
DE	Germany	LU	Luxembourg	US	United States of America
DK	Denmark	MC	Monaco		
ES	Spain	MG	Madagascar		

EDIBLE FAT-CONTAINING PRODUCTS

- 5 The present invention relates to edible fat-containing products comprising an indigestible fat-replacer.

In this specification, unless otherwise indicated, the term 'fat' refers to edible fatty substances in a general sense, including natural or synthesized fats and oils consisting essentially of triglycerides such as, for example, soybean oil, sunflower oil, palm oil, coconut oil, fish oil, lard and tallow, which may have been partially or completely hydrogenated or modified otherwise, as well as non-toxic fatty materials having properties similar to triglycerides, herein referred to as fat-replacers, which materials may be partially or fully indigestible. The terms fat and oil are used interchangeably.

- 20 Over the last decade many non-triglyceride fatty substances have been described as potential fat-replacers in food products. Examples thereof are waxes, e.g. jojoba oil and hydrogenated jojoba oil, polysiloxanes, acylated glycerides, polyalkoxyglycerolethers, dicarboxylic acid esters, polyol fatty acid polyesters and the epoxy extended derivatives thereof. Examples of disclosures of fat-replacers are e.g. DD 207 070, Journal of Food Science 49, 419-428 (1984), US 3,600,186, US 4,005,195, US 4,005,196, US 4,034,083, US 4,582,715, US 4,582,927, EP 0 233 856, EP 0 236 288, EP 0 235 836 and EP 0 254 547.

In particular polyol fatty acid polyesters, and more specifically the sugar fatty acid polyesters, such as e.g. the sucrose fatty acid polyesters, are receiving increased attention as low-calorie fat-replacers in edible products. Substantially indigestible for human beings they have physical and organoleptic properties very similar to

triglyceride oils and fats conventionally used in edible products.

Polyol fatty acid polyesters are also reported to have use as pharmaceutical agents e.g. in view of their ability to take up fat-soluble substances, such as in particular cholesterol, in the gastro-intestinal tract, and subsequently remove those substances from the human body.

10 Suitable polyol fatty acid polyesters are derived from aliphatic or aromatic polyols which comprise at least four free hydroxyl groups. Such polyols in particular include the group of sugar polyols, which comprises the sugars, i.e. the mono-, di- and polysaccharides, the corresponding sugar alcohols and
15 the derivatives thereof having at least four free hydroxyl groups. Examples of sugar polyols include glucose, mannose, galactose, xylose, fructose, sorbose, tagatose, ribulose, xylulose, maltose, lactose, cellobiose, raffinose, sucrose, erythritol, mannitol, lactitol, sorbitol, xylitol and alpha-
20 methylglucoside. A particularly preferred polyol is sucrose.

The term 'polyol fatty acid polyester' is intended to refer to any such polyesters or mixtures thereof which have a degree of conversion of 70 % or more, i.e. of which, on an
25 average, 70 % or more of the polyol hydroxyl groups have been esterified with fatty acids. Preferred polyol fatty acid polyesters for use in the present invention have degrees of conversion of 85 % or more, or even 95 % or more.

30 The fatty acid residues in the polyol fatty acid polyesters may be derived from naturally occurring or synthetic fatty acids per se, or suitable sources thereof, such as natural triglyceride fats and oils or their corresponding lower-alkyl esters. The fatty acids may be saturated or unsaturated,
35 branched or straight fatty acids containing from 8 to 24 carbon atoms, in particular 12 to 18 carbon atoms, such as

lauric, myristic, palmitic, stearic, oleic, elaidic, and linoleic acids. Suitable natural sources are the vegetable oils, such as sunflower, safflower, rapeseed, cottonseed, palm kernel, palm and soybean oils. Also other oils, for example marine oil or animal oil may be used. If so required, conventional techniques may be used to first introduce the necessary degree of saturation. Suitable such techniques include full or partial hydrogenation, interesterification, and fractionation, and may be used before or after conversion to the polyol fatty acid polyesters.

Two problems sometimes occur with low calorie food containing polyol fatty acid polyesters: if liquid polyol fatty ester acids are used this may result in undesired anal leakage problems, while if more solid polyol fatty esters are used this may provide an undesirably waxy mouthfeel. Other problems sometimes encountered with polyol fatty acid polyesters concern the rheology of the material, the availability of the materials from which the polyol fatty acid esters are made and the complicated processing to prepare polyol fatty acid esters.

EP 233,856 (P&G) discloses the use of intermediate melting polyol fatty acid polyesters for reducing problems of anal leakage and mouthfeel. However, food products fried in these intermediate melting polyol fatty acid polyesters, still have a more waxy mouthfeel than products fried in triglyceride frying media.

Another method to reduce the anal leakage and mouthfeel problems is to use a polyol fatty acid polyester blend consisting of a liquid polyol fatty acid polyester and a solid -hardstock- polyol fatty acid polyester, optionally in combination with digestible fatty materials such as triglycerides.

WO 91/15960 (P&G) discloses specific hardstock materials which may be used in blends of liquid and solid polyol fatty acids. These hardstock materials contain high levels of C₂₀ or higher saturated fatty acid materials. Similar hardstock materials are disclosed in WO 91/15961, WO 91/15963 and WO 91/15964 (P&G).

WO 91/15962 discloses the use of from 10 to 40% of solid polyol fatty acid polyester materials in combination with 60 to 90% liquid non-digestible oils. Preferred solid materials comprise 84.8% of saturated C₁₈ fatty acids.

It has now been found that other suitable combinations of liquid indigestible fatty materials and solid polyol fatty acid polyesters can be obtained. In particular it has been found that advantageous combinations of liquid and solid polyol fatty acid polyesters satisfy one or more of a set of specific conditions.

Accordingly the present invention relates to an edible composition comprising fatty substances, said fatty substances comprising a mixture comprising from 60-99% by weight of the mixture of liquid polyol fatty acid polyesters and from 1-40% by weight of the mixture of solid polyol fatty acid polyesters, characterised in that one or more of the following requirements are satisfied:

(a) the solid polyol fatty acid polyester contains at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues and the solid polyol fatty acid polyester has a beta-prime crystal morphology;

(b) the solid polyol fatty acid polyester is present at a level of less than 20% by weight of the mixture and has an average particle size of less than 20 μ m;

(c) the fatty substances of the composition, together have a thixotropic area of less than 200,000 Pa/s, and the solid polyol fatty acid polyester comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues, the weight ratio of C₁₆ to C₁₈ saturated fatty acid residues being from 5:1 to 1:5;

(d) the fatty substances of the composition, together have a thixotropic area of more than 200,000 Pa/s, and the solid polyol fatty acid polyester comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues, and the wt% of C₁₈ saturated fatty acid residues in the solid polyol fatty acid polyester is less than 90 wt%;

(e) the level of solid polyol fatty acid polyesters is from 1 to 9% by weight of the mixture and the solid polyol fatty acid polyester material comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues.

For the purpose of this invention, throughout this specification wt% for the fatty acid residues are based on the total weight of fatty acid residues in the solid polyol fatty acid polyester material.

Edible compositions in accordance to the invention comprise fatty substances. As indicated above the term fatty substance refers to edible fatty substances which may be fully or partially indigestible. Apart from the liquid and solid polyol fatty acid polyesters as defined hereinbelow, compositions of the invention may comprise digestible fatty substances such as triglyceride materials and non-glyceride fatty substances.

The level of these fatty substances other than the polyol fatty acid polyesters may be up to 90 wt%, based on the total weight of the fatty substances, preferably, however the level

is from 0-40 wt%, more preferred 0-10 wt%, most preferred edible compositions of the invention are substantially free from fatty substances other than polyol fatty acid polyesters.

5

Depending on the type of edible composition, the total level of fatty substances in the edible composition of the invention may be from 1-100 wt%, for example 5-95 wt%. Some edible compositions like shortenings, chocolate and dressings
10 may comprise relatively high levels of fatty substances, for example 30-90 wt%. Other edible compositions like sauces, soups, bakery products etc may comprise lower levels of fatty substances for example 1-30 wt%.

15 In any case, the fatty substances which are present in the edible compositions of the invention comprise a mixture of liquid and solid polyol fatty acid polyester materials, the level of liquid polyol fatty acid polyesters in the mixture being from 60-99 wt%, more preferred 70-97 wt%, most
20 preferred 80-95 wt% and the level of solid polyol fatty acid polyesters being from 1-40 wt%, more preferred 3-30 wt%, most preferred 5-20 wt%, the percentages being based on the total weight of the mixture of liquid and solid polyol fatty acid polyesters.

25

The liquid polyol fatty acid polyester material may be any material which in physical properties and rheology behaves similar to conventional liquid materials and which has a complete melting point below 35°C, more preferred below 30°C,
30 most preferred less than 20°C. Examples thereof are given in the examples. Also mixtures of liquid polyol fatty acid polyesters may be used as the liquid component of the mixture.

35 The solid fatty acid polyester material may be any material satisfying one or more of the requirements of the invention

and which has a complete melting point above 35°C, more preferred above 40°C most preferred above 45°C. Examples of solid materials are given in the examples. Also mixtures of solid polyol fatty acid polyesters may be used.

5

The mixture of liquid and solid polyol fatty acid polyesters hence is preferably characterised by the presence of at least two peaks as measured with differential scanning calorimetry, one of the peaks below 35°C and one of the peaks above 35°C, 10 more preferably one peak below 30°C and one above 40°C, most preferred one peak below 25°C and one above 45°C.

The optional conventional fat-component may be triglyceride oils or fats of animal or vegetable origin. Suitable 15 conventional triglyceride fats and oils include, optionally partially or fully hydrogenated, coconut oil, palmkernel oil, palm oil, marine oils, lard, tallow fat, butter fat, cocoa butter fat, soybean oil, safflower oil, cotton seed oil, rapeseed oil, corn oil sunflower oil and mixtures thereof. 20

In any case at least one of the conditions (a) to (e) as indicated above are satisfied.

In a first aspect of the invention, the solid polyol fatty 25 polyester contains at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues and the solid fatty acid has a beta-prime crystal morphology. Although applicants do not wish to be bound by any theory it is believed that these particular solid polyol fatty acid polyester materials comprising a 30 minimum amount of saturated C₁₂₋₁₈ fatty acid residues and which exhibit beta-prime morphology are particularly advantageous because these materials are believed to be capable of network formation in the liquid /solid mixtures, therewith providing anti-leakage properties and/or improved 35 rheology.

Preferably the level of saturated C₁₂₋₁₈ fatty acid residues in the solid polyol fatty acid polyester is from 10-100 wt%, more preferred 60-100%, most preferred 80-100%.

- 5 The solid polyol fatty acid polyester has a beta-prime morphology. For the purpose of this invention this means that beta prime morphology can be shown to be present with conventional techniques. Preferably at least 10 wt%, more preferred more than 25%, most preferred from 50-100% of the solid polyol fatty acid polyester is present in the form of
10 beta-prime crystals. The presence of these crystals can be detected by known techniques such as X-ray diffraction.

- In a second embodiment of the invention the solid polyol
15 fatty acid polyester material is present at a level of less than 20% by weight of the mixture of polyol fatty acid ester materials, more preferred from 2-15%, most preferred from 3-10% and has an average particle size of less than 20 μm , more preferred from 0.01 to 10 μm , most preferred from 0.1 to 7
20 μm . It is believed that these relatively low levels of solid polyol fatty acid polyester materials combined with their small particle size, again give rise to the formation of a network structure in the liquid/solid mixtures of the invention therewith providing anti-leakage properties and/or
25 improved rheology and/or improved non-waxy mouthfeel and/or reduced graininess. It is believed that higher levels of these small size solid polyol fatty acid polyester materials are less preferred, because they may result in too hard fatty substances. The average particle size can advantageously be
30 measured by conventional techniques, such as light microscopy; preferably prior to measurement of the particle size the sample is subjected to moderate shear for temporarily breaking up a network system that might eventually be present.

35

In a third embodiment of the invention the fatty substances of the composition, together have a thixotropic area of less than 200,000 Pa/s (preferred 10,000 to 100,00, more preferred 15,000 to 50,000 Pa/s), and the solid polyol fatty acid polyester comprises at least 10 wt%, more preferred 20-90%, most preferred 30-80% of C₁₂₋₁₈ saturated fatty acid residues, the weight ratio of C₁₆ to C₁₈ saturated fatty acid residues being from 5:1 to 1:5. In this context it is believed that should the fatty substances of the composition together have a relatively low thixotropic area, then the network formation to provide good rheology and/or mouthfeel and/or anti-leakage is best safeguarded if the level of C₁₂₋₁₈ saturated fatty acid residues in the solid polyol fatty acid polyester is at least 10 wt% and the ratio of C₁₆ to C₁₈ is from 5:1 to 1:5 more preferred from 3:1 to 1:3, most preferred 2:1 to 1:2. The thixotropic area of the composition can be determined by any conventional method, preferably the method as described in WO 91/15962 is used. Another preferred method is described in the examples.

20 In a fourth aspect of the invention the fatty substances of the composition, together have a thixotropic area of more than 200,000 Pa/s, and the solid polyol fatty acid polyester comprises at least 10 wt% more preferred 20-90%, most preferred 30-80% of C₁₂₋₁₈ saturated fatty acid residues, and the wt% of C₁₈ saturated fatty acid residues in the solid polyol fatty acid ester material is less than 90 wt%, more preferred less than 87%, most preferred less than 80% of the fatty acid ester residues. In this context it is believed that should the fatty substances of the composition, together have a relatively high thixotropic area, then the network formation to provide good rheology and/or mouthfeel and/or anti-leakage is best safeguarded if the level of fatty acid residues in the solid polyol fatty acid polyester of C₁₂₋₁₈ saturated fatty acids is at least 10 wt%, provided the level of C₁₈ saturated fatty acid residues is less than 90 wt%.

In a fifth aspect of the invention the level of solid polyol fatty acid polyesters is from 1 to 9% by weight of the mixture of polyol fatty acid polyester materials and the solid polyol fatty acid polyester material comprises at least 5 10 wt%, more preferred 20-80%, most preferred 30-70% of C₁₂₋₁₈ saturated fatty acid residues. It is believed that these relatively low levels of solid polyol fatty acid polyesters with relatively high levels of C₁₂₋₁₈ saturated fatty acids are capable of providing advantageous network properties 10 resulting in good rheology and/or anti-leakage and/or non-waxy mouthfeel.

According to the third-fifth embodiments as described above, the solid polyol fatty acid polyester comprises a certain 15 minimum level of saturated fatty acid residues. For some applications, however it may be advantageous to use -within the constraints as given - fairly high levels of unsaturated fatty acid residues. For some applications the level of unsaturated fatty acid residues in the solid polyol fatty 20 acid ester may in theory be up to 100%, although generally lower levels, for example 0-60 wt% or 10-40 wt% will be used.

In another preferred embodiment of the invention the level of C₂₀ or higher fatty acid residues in the solid polyol fatty 25 acid polyester is preferably less than 60 wt%, more preferred less than 40%, most preferred from 0-10%.

Preferred embodiments of the invention relate to compositions satisfying two or more of the above mentioned conditions. For 30 example preferred edible compositions satisfy at least one requirement of the group of (a) and (b) plus at least one requirement of the group of (c), (d) and (e). Especially preferred are compositions satisfying both requirements (a) and (b), most preferred in combination with at least one of 35 the requirements of (c), (d) and (e).

- In terms of rheology the selection of the appropriate fat-replacer or mixture of fat-replacer and conventional fat strongly depends upon the particular application envisaged, and may range of fat-replacers having a fully fluid rheology to replace liquid oils in e.g. salad, frying or seasoning oils, to more viscous or even solid rheology in compositions having a more structured fat phase such as margarines, spreads, shortenings and confectionery products.
- 10 The present invention is not specific to edible fat-containing compositions in any particular food area. It may be suitably be applied to food products such as spreads, margarines, creams, salad oils, frying oils, shortenings, bakery products such as doughs, cakes and biscuits, fried and
- 15 snack products, fresh, hard and processed cheeses, meat emulsions, mayonnaise and dressings, confectionery products, such as desserts, fillings, chocolates, candies, chews, and ice-creams.

Example I

In the examples the following liquid polyol fatty acid ester is used:

	spe1
5 Fatty acid	weight%
Lauric acid	0.2
Myristic acid	0.2
Palmitic acid	11.8
Stearic acid	8.6
10 Arachidic acid	0.3
Oleic acid	53.8
Elaidic acid	-
Linoleic acid	22.9
Linolenic acid	1.0
15 others	1.2

The octaester content of this material is 78.1%, the OH value 6.1 and the clearpoint as measured with DSC of about 20°C.

20 The following solid polyol fatty acid polyesters are used:

	spe2	spe3	spe4	spe5
<u>Fatty acid</u>	<u>weight%</u>			
Caprylic acid	-	-	-	18.5
25 Lauric acid	0.3	0.3	0.1	0.1
Myristic acid	0.3	1.4	8.3	0.1
Palmitic acid	12.5	48.9	28.8	39.4
Stearic acid	86	48.9	24.5	41.6
Arachidic acid	0.5	0.4	23.1	0.2
30 Oleic acid	-	-	-	-
Elaidic acid	-	0.1	-	-
Linoleic acid	-	-	-	-
Linolenic acid	-	-	-	-
Behenic acid	-	-	12.1	-
35 others	0.4	0.3	3.1	0.1

Spe 2 has a OH value of 3.4 and a clearpoint (DSC) of 59.5°C; spe3 has a OH-value of 4.1 and a clearpoint (DSC) of 55 °C.

Example II

5 A mixture of 90 wt% of spe1 and 10 wt% spe2 is plastized in 2 scraped tubular surface heat exchangers (A-units). The A-units had a volume of 18 ml, a split of 3 ml and 2 scraper blades. The speed of the rotating blades amounted to 500 rpm, at a throughput of 3 kg/hr. The system is cooled to have an outlet temperature of the first A-unit of 41°C and 20°C for the second A-unit. The average particle size as determined by light microscopy (sample of 0.01 mm thickness prepared in a 0.01 m Leitz culture chamber, measured with polarized light at ambient temperature magnification 100 times, resolution about 1 μm) was less than 10 μm (estimated 4-6 μm).

The thixotropic area of the sample at 33.3 °C was significantly less than 200,000 Pa/s and was determined as follows:

20 The sample is tempered by pouring 5 g of fatty substance after melting in glass-tubes (diameter 10 mm, wall thickness 1 mm) followed by heating to 80°C for 30 minutes. The heated sample is then cooled in a water bath of 5°C until a temperature is reached of 29.4°C. The cooled sample is then stored for 1 week at 21.1°C. The thixotropic area of the sample is then determined as follows: The viscometer is kept at 33.3°C, the temperature of the sample is adjusted to this temperature. The shear rate is linearly increased from 0 s⁻¹ to 800 s⁻¹ in 2 minutes and then reduced back to 0 s⁻¹ in another 2 minutes in a Ferranti Shirley viscometer. The thixotropic area is the area encompassed by the hysteresis loop in the shear rate versus the shear stress plot.

Example III

Example II was repeated when using a mixture of 90% spe1 and 10% of spe3. Again the average particle size of the hardstock material was less than 10 μm and the thixotropic area was far less than 200,000 Pa/s.

Example IV

A mixture of 92 wt% spe1 and 8 wt% spe3 was prepared and crystallised by cooling to 20°C with tap water in a stirred vessel (content 50g). The thixotropic area was determined as in example II and was far less than 200,000 Pa/s. Similar results were obtained for mixtures of 92 wt% spe1 and 8 wt% spe4 or spe5., and mixtures of 70% spe1 and 30% of spe2 or spe3.

Example V

A mixture of 73 wt% of trans-hardened soybean oil (slip melting point 36°C), 4% fully hardened palm oil, 21 wt% spe1 and 2 wt% spe3 was prepared. The thixotropic area was determined as in example II and was significantly more than 200,000 Pa/s.

Similar results were obtained with the following mixtures:

- (a) 63 wt% trans-hardened palm oil, (slip melting point 44°C), 4 wt% fully hardened palm oil, 31 wt% spe1 and 2 wt% spe3.
- (b) 63 wt% trans-hardened palm oil (slip melting point 44°C), 2 wt% fully hardened palm oil, 33 wt% spe1 and 2 wt% spe3.
- (c) 63 wt% trans-hardened palm oil (slip melting point 44°C), 35 wt% spe1 and 2 wt% spe3.

Example VI

A sample of sucrose octastearate was crystallised into beta prime structure, according to the method as described in
5 Jandacek and Webb, Chemistry and Physics of Lipids (1978) 163-176.

A mixture was prepared of 65 wt% spel and 35 wt% of the sucrose octastearate. The mixture is evaluated by X-ray
10 diffraction and shows beta prime crystal morphology.

CLAIMS

1. An edible composition comprising fatty substances, said fatty substances comprising a mixture comprising from 60-99%
5 by weight of the mixture of liquid polyol fatty acid esters and from 1-40% by weight of the mixture of solid polyol fatty acid esters, characterised in that one or more of the following requirements are satisfied:
- 10 (a) the solid polyol fatty acid polyester contains at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues and the solid polyol fatty acid polyester has a beta-prime crystal morphology;
- 15 (b) the solid polyol fatty acid polyester is present at a level of less than 20% by weight of the mixture and has an average particle size of less than 20 μ m;
- 20 (c) the fatty substances of the composition, together have a thixotropic area of less than 200,000 Pa/s, and the solid polyol fatty acid polyester comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues, the weight ratio of C₁₆ to C₁₈ saturated fatty acid residues being from 5:1 to 1:5;
- 25 (d) the fatty substances of the composition, together have a thixotropic area of more than 200,000 Pa/s, and the solid polyol fatty acid polyester comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues, and the wt% of C₁₈
30 saturated fatty acid residues in the solid polyol fatty acid polyester is less than 90 mole%;
- 35 (e) the level of solid polyol fatty acid polyesters is from 1 to 9% by weight of the mixture and the solid polyol fatty acid polyester material comprises at least 10 wt% of C₁₂₋₁₈ saturated fatty acid residues.

2. Edible composition according to claim 1, wherein at least two of the requirements (a)-(e) are satisfied.
3. Edible composition according to claim 1 or 2 , wherein
5 the fatty substances comprise from 10-100% of polyol fatty acid esters.

International Application No

1. CLASSIFICATION OF SUBJECT MATTER (if several classification symbols apply, indicate all)⁶

Int. Cl. 5 A23D9/00; A23L1/308; A23G3/00; A23G9/02

Minimum Documentation Searched?

Classification Symbols

A23D : A23L

**Documentation Searched other than Minimum Documentation
to the Extent that such Documents are Included in the Fields Searched⁸**

Category °	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	EP,A,0 375 027 (THE PROCTER & GAMBLE COMPANY) 27 June 1990	1,3
Y	see page 2, line 39 - page 3, line 8; claims 1,3,5-10 see page 7, line 3-6 see page 9, line 22 - line 26 ---	1-3
P,Y	WO,A,9 115 964 (THE PROCTER & GAMBLE COMPANY) 31 October 1991 cited in the application see page 7, line 12 - page 8, line 10; claims 1-3 see page 10, line 28 - page 11, line 14 see page 14, line 23 - line 25 --- -/--	1-3

"A" document member of the same patent family

09.09.92

Signature of Authorized Officer

Signature of Authorized Officer
KANEELAND

Mme Dagmar FRANK

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category °	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
Y	EP,A,0 233 856 (THE PROCTER & GAMBLE COMPANY) 26 August 1987 cited in the application see page 15, line 7-12; claims 1,2,5,6; examples 1,2 see page 23; table 1 see page 16, line 10 - line 16 ---	1-3
A	US,A,4 005 195 (THE PROCTER & GAMBLE COMPANY) 25 January 1977 cited in the application see column 5, line 58 - line 64; claims 1-10,19,20,22,25,31,43; example 6 see column 6, line 7 - line 20 ---	1-3

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO. EP 9201429
SA 61057**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 19/08/92

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP-A-0375027	27-06-90	AU-A- 4716189	28-06-90
		CA-A- 2004723	22-06-90
		JP-A- 3139240	13-06-91
		US-A- 5102683	07-04-92
WO-A-9115964	31-10-91	US-A- 5085884	04-02-92
		AU-A- 7789091	11-11-91
EP-A-0233856	26-08-87	AU-B- 602674	25-10-90
		AU-A- 6954487	01-09-88
		JP-A- 63222671	16-09-88
US-A-4005195	25-01-77	BE-A- 851328	11-08-77
		CA-A- 1083043	05-08-80
		DE-A, C 2705105	18-08-77
		FR-A, B 2340737	09-09-77
		GB-A- 1579241	19-11-80
		JP-C- 1491850	07-04-89
		JP-A- 52120131	08-10-77
		JP-B- 63039568	05-08-88
		LU-A- 76751	19-08-77
		NL-A- 7701460	16-08-77